
## **SWARF CONTAINER TYPE SGU**









## Specially designed to separate liquids from solids and collect them

- perforated intermediate screen 100 mm above the floor, perforation Ø 3 mm, separation 6 mm
- 1" drain-cock for drainage of liquids
- can be emptied at any height by cable operated from the driver's seat
- body with all-round reinforced edging
- sturdy frame with fork sleeves
- can be secured to prevent slipping and unintentional emptying
- welding, oil and watertight

## Accessories

- 2 swivel + 2 fixed polyamide castors
  Ø 180 mm, one swivel castor with brake
   construction height 225 mm
- galvanized lid, can be opened from both sides
- pick-up for a crane, lever troller and pallet truck
- adjustable dumping brake from size SGU 50 upwards

## Individual construction on request e.g.

- pick-up for bale gripper
- supporting feet for use with a pallet truck



Dimensions

in mm (I x w x h)

1440 x 680 x 580

1440 x 780 x 680

1440 x 1280 x 680

1640 x 1280 x 780

1640 x 1280 x 1090

1640 x 1680 x 1090



SGU with castors

**SGU 30** 

SGU 50

**SGU 75** 

SGU 100

SGU 150

SGU 200

Finish:

Volume

(approx.) in m<sup>3</sup>

0,30

0,50

0,75

1,00

1,50

2,00

SGU with supporting feet

Weight in kg (painted/galv.)

112/121

130 / 140

169 / 182 220 / 237

250 / 270

287 / 308

Fork sleeve inside dimensions in mm

:	A B B		
	Α	В	C
SGU 30	10	200	60
SGU 50	150	200	60
SGU 75-200	495	200	60

Load capacity

in kg

750

1000

1000

1500

1500

1500